

# Punches CONFIX™

for CONFIX™ bulkhead fittings, for steel, aluminium, stainless steel



These punches can be used to punch the special cutout shapes for the CONFIX™ bulkhead fittings.

For max. 2 mm stainless steel (V2A versions), sheet steel, aluminium and plastic.

The punches are suitable for the hand hydraulic punch driver and the hydraulic foot pump. For the FWS-A 50 / FWS-B 48 punches, we only recommend the hydraulic foot pump.

#### Scope of delivery:

- Punch, die, counter nut and draw stud
- robust plastic storage case

## Specifikationer

**Material** Stål, härdat och förbränt

## Fördelar

- For the special cut-out shapes for CONFIX™
- High-quality padded transport case
- Suitable for hand hydraulic punch driver by icotek or other manufacturers

## Produkttyper och storlekar

**Punch FWS-A16/20 / FWS-B11/16**



ArtNr.	<b>80095</b>	Max.	<b>2 mm</b>
EAN	<b>4251269333</b>	väggjocklek	
	<b>316</b>		
Antal	<b>1</b>		
Number of	<b>3</b>		
centre			
punches			
Kompatibel	<b>FWS-A 16,</b>		
med CONFIX™	<b>FWS-A 20,</b>		
FWS	<b>FWS B11,</b>		
	<b>FWS-B 16</b>		
Tråd UNF	<b>19 mm</b>		
Stansbart	<b>Plast, stål</b>		
material	<b>(St)</b>		



ArtNr.	<b>80195</b>	Max.	<b>2 mm</b>
EAN	<b>4251269333</b>	väggjocklek	
	<b>354</b>		
Antal	<b>1</b>		
Number of centre punches	<b>3</b>		
Kompatibel med CONFiX™ FWS	<b>FWS-A 16, FWS-A 20, FWS B11, FWS-B 16</b>		
Tråd UNF	<b>19 mm</b>		
Stansbart material	<b>Rostfritt stål V2A</b>		



ArtNr.	<b>80096</b>	Max.	<b>2 mm</b>
EAN	<b>4251269333</b>	väggjocklek	
	<b>323</b>		
Antal	<b>1</b>		
Number of centre punches	<b>3</b>		
Kompatibel med CONFiX™ FWS	<b>FWS-A 25, FWS-B 21</b>		
Tråd UNF	<b>19 mm</b>		
Stansbart material	<b>Plast, stål (St)</b>		

Punch FWS-A 25 / FWS-B 21 V2A



ArtNr.	<b>80196</b>	Max.	<b>2 mm</b>
EAN	<b>4251269333</b>	väggjocklek	
	<b>361</b>		
Antal	<b>1</b>		
Number of centre punches	<b>3</b>		
Kompatibel med CONFIX™ FWS	<b>FWS-A 25, FWS-B 21</b>		
Tråd UNF	<b>19 mm</b>		
Stansbart material	<b>Rostfritt stål V2A</b>		

Punch FWS-A 32 / FWS-B 29



ArtNr.	<b>80097</b>	Max.	<b>2 mm</b>
EAN	<b>4251269333</b>	väggjocklek	
	<b>330</b>		
Antal	<b>1</b>		
Number of centre punches	<b>4</b>		
Kompatibel med CONFIX™ FWS	<b>FWS-A 32, FWS-B 29</b>		
Tråd UNF	<b>19 mm</b>		
Stansbart material	<b>Plast, stål (St)</b>		



ArtNr.	<b>80197</b>	Max.	<b>2 mm</b>
EAN	<b>4251269333</b>	väggjocklek	
	<b>378</b>		
Antal	<b>1</b>		
Number of centre punches	<b>4</b>		
Kompatibel med CONFiX™ FWS	<b>FWS-A 32, FWS-B 29</b>		
Tråd UNF	<b>19 mm</b>		
Stansbart material	<b>Rostfritt stål V2A</b>		



ArtNr.	<b>80098</b>	Max.	<b>2 mm</b>
EAN	<b>4251269333</b>	väggjocklek	
	<b>347</b>		
Antal	<b>1</b>		
Number of centre punches	<b>4</b>		
Kompatibel med CONFiX™ FWS	<b>FWS-A 40, FWS-B 36</b>		
Tråd UNF	<b>19 mm</b>		
Stansbart material	<b>Plast, stål (St)</b>		



ArtNr. **80198** Max. **2 mm**  
EAN **4251269333** väggjocklek  
**385**  
Antal **1**  
Number of **4**  
centre punches  
Kompatibel **FWS-A 40,**  
med CONFiX™ **FWS-B 36**  
FWS  
Tråd UNF **19 mm**  
Stansbart **Rostfritt stål**  
material **V2A**



ArtNr. **80099** Max. **2 mm**  
EAN **4251269333** väggjocklek  
**255**  
Antal **1**  
Number of **4**  
centre punches  
Kompatibel **FWS-A 50,**  
med CONFiX™ **FWS-B 48**  
FWS  
Tråd UNF **19 mm**  
Stansbart **Plast, stål**  
material **(St)**



ArtNr.	<b>80199</b>	Max.	<b>2 mm</b>
EAN	<b>4251269333</b>	väggjocklek	
	<b>262</b>		
Antal	<b>1</b>		
Number of centre punches	<b>4</b>		
Kompatibel med CONFiX™	<b>FWS-A 50, FWS-B 48</b>		
FWS			
Tråd UNF	<b>19 mm</b>		
Stansbart material	<b>Rostfritt stål V2A</b>		